

Polywater® FTTx

Cable Pushing/Pulling Lubricant



Polywater® FTTx Fiber Lubricant makes the installation of fiber drops easy. The lubricant is concentrated; only a thin film is required for immediate tension reduction that lasts even as the lubricant dries. Spray or wipe the cable or conduit. Quick and easy to use without mess or excess lubricant. Works well for placing fiber in HDD-installed conduit.

- Perfect for Fiber Optic Drops (FTTx)
- Easy Application with Spray or Wipe
- Lubricates with Very Thin Film, Performs After Drying
- Use for Push or Pull
- Non-Staining, Quick Clean-Up
- Compatible with Common Cable Jackets - Including Polyethylene

Application and Usage Recommendations



Polywater® FTTx Spray Lubricant remains effective with very thin, molecular-level films, so it continues to lubricate even when it cannot be detected.

Polywater® FTTx Lubricant is easy to apply. It can be sprayed into conduit or wiped onto cable, making the installation of multiple drops quick and convenient. Use Polywater® FTTx lubricant for better installations without having to handle bulky pails on shorter runs or in small enclosures.

Spray

Inject 5 to 10 sprays directly into conduit just before pulling or pushing. For larger conduit or longer pulls, spray additional lubricant onto the cable or into the conduit during the pull to reduce the tension throughout the length of the pull.

Wipe

Wipe cable as it enters conduit or attach wipe to pulling line to prelubricate conduit. One towel is sufficient for small cable and for installations or drops of less than 200 feet. Use additional lubricant wipes on longer pulls or when tension increases.

Polywater® FTTx Lubricant Ordering Information

Part #	Description	Case Quantity
FTTx-35LR	1-Qt (.95 liter) Bottle with Pump Sprayer	12/Case
FTTx-D20	Canister with 20 saturated wipes	12 Canisters/Case

Copyright © 2006. American Polywater Corporation. All Rights Reserved

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

Lit-FXFLYER/7-06/CURTIS/7-06

Makers of Polywater® J and Dyna-Blue® Cable Lubricants and Pull-Planner™ 2000 Software

**American
Polywater®
Corporation**

P.O. Box 53
Stillwater, MN 55082
U.S.A
1-800-328-9384

custserv@polywater.com (e-mail)
www.polywater.com (URL)

1-651-430-2270
fax 1-651-430-3634