



## SWIVELS & SHACKLES

289 Rosebank Road,  
Avondale,  
Auckland 1026  
PH: 09-373-4487,  
FAX: 09-828 2815  
E-MAIL: [sales@phel.co.nz](mailto:sales@phel.co.nz)  
WEB: [www.phel.co.nz](http://www.phel.co.nz)

We stock a wide range of swivels, small brass swivels, Basic ball Bearing Swivels with 2 Shackles attached, Champion 808 Condux Stainless Steel Swivels & Condux break away Swivels. It is recommended when conducting a cable pull that you use a swivel to join the Rope to your cable sock to prevent damage to your cable.



**Condux Stainless Steel  
Champion 808 Swivel,**



**Standard Steel Swivel,**



**Condux Breakaway**

Description	Code	Length	Dia	Max Rope Dia	U/G SWL	O/H SWL
Standard Swivel 500kg	30331	75mm	28.5mm	16mm	500kg	300kg
Standard Swivel 1.5T	30332	135mm	45mm	20mm	1500kgs	900kgs
Standard Swivel 3.0T	30333	190mm	65mm	30mm	3000kgs	1800kgs
Champion 808 270kg	08017000	90mm	16mm	7mm	270kgs	162kgs
Champion 808 1100kg	08016000	115mm	22mm	10mm	1100kgs	660kgs
Champion 808 2250kg	08080912	138mm	32mm	14mm	2250kgs	1350kgs
Champion 808 3150kg	08080913	133mm	35mm	14mm	3150kgs	1890kgs
Champion 808 4500kg	08080916	165mm	41mm	16mm	4500kgs	2700kgs
Champion 808 6800kg	08080920	178mm	51mm	19mm	6800kgs	4080kgs
Champion 808 11340kg	08080925	260mm	64mm	25mm	11340kgs	6804kgs
Champion 808 13600kg	08080930	306mm	76mm	33mm	13600kgs	8160kgs
Breakaway Swivel 16	CONBA16	90mm	16mm	7mm	Various	N/A
Breakaway Swivel 22	CONBA22	115mm	22mm	10mm	Various	N/A
Brass Swivel	SB07	25mm	7mm	8mm	150kgs	N/A
Brass Swivel	SB09	30mm	9mm	8mm	200Kgs	N/A
Brass Swivel	30330	38mm	12mm	8mm	300kgs	N/A



### **Brass Swivels,**

Small Brass Swivels, c/w  
stainless steel shackles

## SHACKLES

289 Rosebank Road,  
Avondale,  
Auckland 1026  
PH: 09-373-4487,  
FAX: 09-828 2815  
E-MAIL: [sales@phel.co.nz](mailto:sales@phel.co.nz)  
WEB: [www.phel.co.nz](http://www.phel.co.nz)



Screwdriver slot type shackles used by Powerhowse Electric Ltd for cable hauling. We stock a large range in Galvanised and Stainless steel, from 4mm Stainless to 22mm Galvanised. These are smooth edged and less likely to catch or jam when hauling cable.

Description	Code	Length	Dia	Max Rope Dia	SWL
Stainless Steel Shackle 4mm	30310	24mm	4mm	8mm	137.5kgs
Stainless Steel Shackle 8mm	30311	44mm	8mm	16mm	700kgs
Stainless Steel Shackle 10mm	30312	55mm	10mm	20mm	1125kgs
Stainless Steel Shackle 12mm	30313	66mm	12mm	24mm	1500kgs
Galvanised Shackle 8mm	SGDM8	46mm	8mm	16mm	655kgs
Galvanised Shackle 16mm	30315	95mm	16mm	30mm	2700kgs
Galvanised Shackle 21mm	30316	124mm	21mm	40mm	3125kgs

### SHACKLE TEST



**1**                      **2**                      **3**                      **4**                      **5**

Item 1, 2, 3 and 4 are commercially graded. Item 5 is High Tensile.

Item	Pin Diameter	Test Till Fail	PHEL Rating
1	8MM	2620KG	655KG
2	11MM	5440KG	1360KG*
3	16MM	10790KG	2700KG
4	21MM	12500KG	3125KG
5	22MM	24400KG	6100KG*

\*No Longer a Stock Item