

2.5 TONNE SELF LOADING TRAILER

The trailer is normally fitted with an air-cooled Honda petrol engine and has a drum capacity of approx 2600mm diameter x 1450mm wide. It will have an 76mmØ spindle complete with stainless steel brake disc & manually adjusted caliper brake, plus 1-set of spindle adapter sleeves. The machine was developed to enable one operator to safely and efficiently **load drums up to 2500kg**.



The Self Loading Cable Trailer is primarily designed for transporting drums of electrical power cable and paying out cable at the work site.The unit has a number of features which improve productivity by permitting safe, one man handling of cable drums.

- The cable trailer need not be positioned accurately to pick up the load. Chains attached to the pickup arms provide the required flexibility.
- Hydraulic power is used to load the trailer and pay out cable at the work site.
- The Drum support shaft is manufactured from high tensile steel tube and can easily be fitted through the cable drum by one person.
- The cable drum shaft rotates on low friction, weather resistant bearings.
- A drum rotator turns the drum to pay out or reel in.

Because the cable trailer has been designed for one man operation, use of the trailer can free personnel for other tasks or allow smaller work groups to maintain effective output.

MAX LOAD MASS	MAX DRUM DIA	MAX DRUM WIDTH	STANDARD SPINDLE DIA	DIMENSIONS L x W x H (MM)	STANDARD TRAILER BRAKE TYPE	WEIGHT
2500kgs	2600mm	1450mm	76mm	4155 x 2500 x 2320	ELECTRIC	1000kgs

Web: www.phel.co.nz *Ph: 0508 734 487* *Email: sales@phel.co.nz*