



289 Rosebank Road,
 Avondale,
 Auckland 1026
 PH: 09-373-4487,
 FAX: 09-828 2815
 E-MAIL: sales@phel.co.nz
 WEB: www.phel.co.nz

Drum Jack 5 & 10 Ton Rated

For Jacks rated 5Ton and over we offer a Ladder Lift style of Drum Jack.

The jacks consist of two ladder units with hydraulic jacks in the base of the lifting section of the jacks.

When loading a drum onto the jacks, position the jacks either side of the drum, push the solid spindle through the nearest ladder hole in line with the centre of the drum centre and into the corresponding ladder hole in the other jack. Once the spindle is in place pump the hydraulic jacks at the base of each jack arm to raise the drum.

This series of Drum Jacks are supplied with a solid spindle and 2 hollow stabiliser bars.

Note when setting up the Ladder Lift Jacks it is important to fit the stabiliser bar into the base of the jacks.



SIZE	DRUM RADIUS	DRUM DIA
5	1300MM	2600MM
10	1700MM	3400MM



To keep the drum in place whilst being used on the ladder lift style of jacks we also have Spindle Spacer Locks. These bolt onto the spindle both ends of the drum and keep the drum in place whilst on the spindle. We have these spacer locks in various sizes to suit the various size spindles