

Gulfstream[™] 150 Micro Fiber Blower

The Gulfstream 150 micro fiber blower is designed for FTTx and Enterprise micro fiber installation projects. The self-contained Gulfstream 150 combines the push force of an electric driven belt with compressed air to quickly and easily install microfiber cables from 1.0mm to 2.5mm in diameter into microduct ranging from 5mm to 8.0mm - at speeds up to 375 feet per minute!

The unit's machined aluminum construction provides a lightweight profile with long life and durability. The Gulfstream 150's compact size and convenient carrying case allow for easy transport between job sites.

Gulfstream[™] 150 Micro Fiber Blower Complete Kit

Part Number	Description
08783400-50	Gulfstream 150 [™] Micro Fiber Blower Standard Kit, US
08783400-51	Gulfstream 150 [™] Micro Fiber Blower Standard Kit, Int'l
08783400-53	Gulfstream 150 [™] Micro Fiber Blower Base Kit, US
08783400-55	Gulfstream 150™ Micro Fiber Blower Base Kit, Int'l

Included in standard kits:

Part Number	QTY	Description
08783054	1	Plastic Case
02291020	1	Hex Key Set
08783426	2	Small Groove Wheel
08783076	1	Seal Kit
08783077	1	O-Ring Kit (qty 5)
02290882	1	Adjustable Tripod, 9lbs, 11" - 63"
02291088	1	3 Pin Cordset
08783026	1	Belt Battery Clip
08783259	1	Blank Seal Kit (qty 6)

Includes cable seals and duct packs on reverse side

Included in base kits:

Part Number	QTY	Description	
08783054	1	Plastic Case	3-1-1 A
02291020	1	Hex Key Set	
08783426	2	Small Groove Wheel	
08783076	1	Seal Kit	
08783077	1	O-Ring Kit (qty 5)	
02291088	1	3 Pin Cordset	
08783026	1	Belt Battery Clip	
08783259	1	Blank Seal Kit (qty 6)	

Cable Seals, Duct Packs and Tripod are sold individually



Blower Size 🍊

- Dimensions: 8" (h) x 6" (w) x 4"(l)
 203mm (h) x 152mm (w) x 101mm(l)
- Weight: 5lbs/2.27kg

Microduct Range

- 5 8mm
- Built in clamping system with interchangeable seals

Fiber Cable Range

• 1 – 2.5mm

Power System

- Electric drive motor
- Rechargeable battery pack with belt clip
- 12v (US) or 10.8v (EU) Cordless Battery or AC Power Supply (optional)

Drive

- Roller Cover
- Maximum push force: 4.5lbs (20N)
- Speed: 0-375fpm (0 115mpm)

Controls

- Display featuring real time speed and distance
- Forward/Reverse switch
- Speed & torque control

Force and Flow

- Air connections: 1/4" EU or US Coupling
- Air Pressure Requirements (BAR)*: 10-15
- Air Pressure Requirements (PSI)*: 150-205
- Flow Requirements (CMM)*: 0.5-1.5
- Flow Requirements (CFM)*: 10-35

*Air pressure and flow requirements depend on job specifics including duct and fiber size, distance of deployment, etc.

Condux International, Inc. | 145 Kingswood Drive | PO Box 247 | Mankato | MN 56002-0247 | USA t: 1.507.387.6576 • t: 1.800.533.2077 (Toll Free) • t: +44 (0)1728 726529 (Europe, Middle East, Africa) e: cndxinfo@condux.com | www.condux.com





Gulfstream[™] 150 **Micro Fiber Blower Replacement Parts**

Replacement Cable Seals

Part Number	Description	
08783448	1.25mm Cable Seal Kit*	
08783449	1.50mm Cable Seal Kit*	
08783450	1.75mm Cable Seal Kit*	
08783451	2.00mm Cable Seal Kit*	
08783452	2.25mm Cable Seal Kit*	
08783453	2.50mm Cable Seal Kit*	
08783259	Cable Seal Kit Blanks*	

*Included in Gulstream 150 standard blower kit Each Seal Kit Includes 6 Pieces

Duct Packs

Part Number	Description	100.00
08783170	5.0mm Duct Pack Assembly*	
08783171	6.0mm Duct Pack Assembly*	
08783172	7.0mm Duct Pack Assembly*	
08783173	8.0mm Duct Pack Assembly*	

*Included in Gulstream 150 standard blower kit Each Duct Pack Includes 10 O-Rings

Replacement O-Rings

Part Number	Description	
08783190	5.0mm Duct O-Ring Kit	1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
08783191	6.0mm Duct O-Ring Kit	
08783192	7.0mm Duct O-Ring Kit	
08783193	8.0mm Duct O-Ring Kit	

Each O-Ring Kit Includes 12 Pieces

Accessories for Gulfstream[™] 150 Micro Fiber Blower

Part Number	Description	
08783390	Gulfstream™ 150 Flow Regulator	
08783391	Gulfstream [™] 150 Flow Regulator - Intl Fittings	
02290882	Tripod	
08783090	AC Power Supply - Int'l	
08783301	GS150 Proof/Pressure Test Kit	
08783085	A/C Power Supply - US	



Scan here to see our Gulfstream 150 product training video or visit us at www.youtube.com/conduxinternational

Available Locally From:

Condux International, Inc. | 145 Kingswood Drive | PO Box 247 | Mankato | MN 56002-0247 | USA t: 1.507.387.6576 • t: 1.800.533.2077 (Toll Free) • t: +44 (0)1728 726529 (Europe, Middle East, Africa) e: cndxinfo@condux.com | www.condux.com

Advantages

- Single handed operation
- · Self contained electric motor
- Cost effective
- Simple to maintain
- Lightweight (5lbs / 2.27kg)
- Durable long life design .
- Instructional Video

Features

- LCD screen featuring speed, distance and life counter
- Software controlled drive system
- User friendly controls •
- Easy to read air pressure gauge •
- Built in clamping system with interchangeable seals
- Standard QD air compressor connection