



OMAC TRAILERISED WINCHES

Powerhowse Electric imports and supplies a range of different types of Trailerised Winches that are towable and hydraulically operated with variable pulling speed and force. An all-in-one unit winch comes complete with Hauling rope and tensioner. Available with dyneema or steel rope.



CODE	DESCRIPTION	MAX ROPE DIAMETER	DIMENSIONS L x W x H	WEIGHT
UP30	3T UP30 OMAC Winch	12 MM	3600 x 650 x 1600	1400kg
UP40	4T UP40 OMAC Winch	12MM	3880 x 1820 x 1640	1250kg
UP50	5T UP50 OMAC Winch	14MM	3880 x 1820 x 1640	1750kg

3T UP30 OMAC Winch

Max Pull: 30 kN
 Speed at max pull: 16 m/min
 Max Speed: 65 m/min
 Pull at Max Speed: 10 kN
Only Available in Hire

4T UP40 OMAC Winch

Max Pull: 40 kN
 Speed at max pull: 12 m/min
 Max Speed: 65 m/min
 Pull at Max Speed: 5 kN
Available in Hire or Made to Order

5T UP50 OMAC Winch

Max Pull: 50 kN
 Speed at max pull: 13 m/min
 Max Speed: 80 m/min
 Pull at Max Speed: 8 kN
Available in Hire or Made to Order

Web: www.phel.co.nz

Ph: 0508 734 487

Email: sales@phel.co.nz