

# Polywater®

## CLR Lubricant



TRANSPARENT WATER-BASED GEL LUBRICANT



### A Clear and Clean, Easy-to-Apply Cable Pulling Lubricant for Daily Use

Polywater® CLR is a clear, slow-drying, thick gel lubricant that was developed for easy handling and application on all types of wire and cable installations. From electrical service work to data applications, it provides a clean and easy way to finish projects.



#### FEATURES AND BENEFITS

- **CLEAN**  
Clear formula wipes off easily, allowing wire markers to stick
- **NON-STAINING**  
Will not stain clothing, carpet, or sheetrock
- **CLINGS TO CABLE**  
Easy to apply by hand or squeeze onto the cable
- **SAFE**  
Non-toxic and biodegradable water-based lubricant
- **UL/ULC LISTED**  
UL Listed to US and Canadian safety standards

[polywater.com](http://polywater.com) | +1 651-430-2270

# Polywater® CLR Lubricant



CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
CLR-35	1 qt (0.95 L) Bottle	12
CLR-128	1 gal (3.8 L) Pail	4
CLR-640	5 gal (18.9 L) Pail	1



Non-staining lubricant.

## SPECIFICATIONS AND APPLICATIONS

- **Cable Compatibility:** Passes IEEE 1210 physical and electrical testing on a wide variety of cable materials. It does not stress crack polyethylene.
- **Application:** Clings to cable and will not cold flow.
- **Properties:** Dries slippery. Unlike wax lubes, it leaves little residue and will not cement cables to conduit. Contains no wax, grease, or silicone and thus will not propagate a flame.
- **Temperature Use Range:** 20°F to 120°F (-5°C to 50°C).
- **Temperature Stability:** No phase-out after five freeze/thaw cycles or 5-day exposure at 120°F (50°C).

[polywater.com](http://polywater.com) | +1 651-430-2270

**IMPORTANT NOTICE:** The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation LIT-CLRFLYER/REV000

**Polywater®**  
Solutions at work.

American Polywater Corporation  
11222 60th Street N.  
Stillwater, MN 55082 USA

+1 651-430-2270 Main  
+31 10 233 0578 Europe, Middle East, N. Africa  
email: [support@polywater.com](mailto:support@polywater.com)