

# Polywater®

## SpliceMaster® HP™



MULTIPURPOSE SOLVENT CLEANER



## The Most Versatile Cleaner for Electrical Construction and Maintenance Needs

Polywater® SpliceMaster® HP™ is a versatile and popular electrical cleaner for cable splice preparation, cable termination, and electrical apparatus maintenance. It fits the needs of electrical utilities, line contractors, and medium voltage crews needing to comply with regulatory and safety requirements. Polywater SpliceMaster HP is available in a wide range of bulk and kit packaging options to meet various field uses.




### FEATURES AND BENEFITS

- **MULTIPURPOSE**  
From plant shutdowns to substation builds, HP is the only cleaner needed for electrical applications
- **HIGH SOLVENCY**  
Excellent for cable splice preparation and electrical equipment cleaning
- **NO RESIDUE**  
Evaporates completely, leaving no tracking residue
- **SAFE EXPOSURE**  
Contains no carcinogens and replaces chlorinated electrical cleaners
- **NONCONDUCTIVE**  
Will not short across typical electrical voltages

[polywater.com](http://polywater.com) | +1 651-430-2270



CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
HP-1	Saturated 8" x 12" (20 cm x 30 cm) Wipe	144
HP-P158ID	Tandem Pack™ Wet/Dry 5" x 8" (13 cm x 20 cm) Wipe	144
HP-3PS	PEL-PAC® Kit* Contains: 3 – HP-P158ID Wet/Dry Wipes; 1 – Strip 120 Grit Nonconductive Sanding Cloth	10
HP-P63	PEL-PAC Kit* Contains: 6 – HP-P158ID Wet/Dry Wipes; 3 – Strips 120 Grit Nonconductive Sanding Cloth; 1 – Instruction Card	12
HP-T369	PEL-PAC Kit* Contains: 3 – Saturated 6" x 9" (15 cm x 23 cm) Wipes in a Tin	24
HP-T369/S	Same as Kit Above; with Sanding Cloth	24
HP-T369/S-D	Same as Kit Above; Includes Dry Towel	24
HP-D72	72-Count Dispenser of 10" x 12" (25 cm x 30 cm) Wipes	6
HPY-12	16 oz (475 ml) Aerosol Can	12
HP-16LF	1 pt (475 ml) Bottle with Flip Top	12
HP-35LF	1 qt (0.95 L) Bottle with Flip Top	12
HP-128	1 gal (3.8 L) Jug	4
HP-640	5 gal (18.9 L) Can	1
HP-DRUM	55 gal (208 L) Drum	1



\*The PEL-PAC System promotes proper cleaning techniques and limits the use of excess solvent. Pre-saturated wipes contain a carefully measured quantity of solvent and are an excellent way to control vapor. Using a measured solvent quantity on each wipe allows users to maintain vapor levels below occupational exposure limits (OELs). Additionally, this design eliminates spill and ingestion hazards.

## SPECIFICATIONS AND APPLICATIONS



- **Cable Compatibility:** Meets the standard electrical utility test requirements based on IEEE 1493 cable cleaning standard.
- **Dielectric Strength:** >40kV at a 100-mil gap per ASTM D877 standard test method.
- **Flash Point:** >140°F (>60°C) per ASTM D93 standard test method.
- **Residue:** <100 ppm per ASTM D2369 standard test method. Leaves no residue.

[polywater.com](http://polywater.com) | +1 651-430-2270

**IMPORTANT NOTICE:** The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation LIT-HPFLYER/REV000

**Polywater**<sup>®</sup>  
Solutions at work.

American Polywater Corporation  
11222 60th Street N.  
Stillwater, MN 55082 USA

+1 651-430-2270 Main  
+31 10 233 0578 Europe, Middle East, N. Africa  
email: [support@polywater.com](mailto:support@polywater.com)