



# SWIVEL

At Powerhowse Electric, we supply a wide range of Swivels imported from overseas. It is recommended when conducting a cable pull that you use a swivel to join the rope to your cable to prevent damage to you cable. Swivels are not designed to run around bullwheels. Always verify that the swivel size is sized to the pulling harness or grip prior to ordering.

**808 Champion Swivels** is designed specifically for underground and overhead cable pulling applications and can handle all types of utility cables. Precision machined from high-strength stainless steel. They are to be used for cable stringing or pulling only, not to be used for Directional Drilling.

**Breakaway Swivels** is essential for fiber optic and coaxial cable pulling, these swivels have a break load ranging from 150-1,800 pounds. (667-8,006 N) and are designed to separate at  $\pm 5\%$  of their rated break load. If the load rating is exceeded, the interior break pin fractures, the swivel separates, and the cable remains undamaged. Break pin is easily replaceable.



**Champion 808 Condux  
Stainless Steel Swivel**



**Standard Stainless-  
Steel Swivel**



**Condux  
Breakaway Swivel**



**Small Brass Swivels  
with Stainless Steel  
Shackles**

CODE	DESCRIPTION	LENGTH	DIA	MAX ROPE DIA	U/G SWL	O/H SWL
30331	Standard Swivel 500kg	75mm	28.5mm	16mm	500kg	300kg
30332	Standard Swivel 1.5T	135mm	45mm	20mm	1500kgs	900kgs
30333	Standard Swivel 3.0T	215mm	65mm	30mm	3000kgs	1800kgs
08017000	Champion 808 270kg	90mm	16mm	7mm	270kgs	162kgs
08016000	Champion 808 1100kg	115mm	22mm	10mm	1100kgs	660kgs
08080912	Champion 808 2250kg	138mm	32mm	14mm	2250kgs	1350kgs
08080913	Champion 808 3150kg	133mm	35mm	14mm	3150kgs	1890kgs
08080916	Champion 808 4500kg	165mm	41mm	16mm	4500kgs	2700kgs
08080920	Champion 808 6800kg	178mm	51mm	19mm	6800kgs	4080kgs
08080925	Champion 808 11340kg	260mm	64mm	25mm	11340kgs	6804kgs
08080930	Champion 808 13600kg	306mm	76mm	33mm	13600kgs	8160kgs
CONBA16	Breakaway Swivel 16	90mm	16mm	7mm	Various	N/A
CONBA22	Breakaway Swivel 22	115mm	22mm	10mm	Various	N/A
SB07	Brass Swivel w/ Shackles	25mm	7mm	8mm	150kgs	N/A
SB09	Brass Swivel w/ Shackles	30mm	9mm	8mm	200Kgs	N/A
30330	Brass Swivel w/ Shackles	38mm	12mm	8mm	300kgs	N/A



## SWIVEL

Introducing SLINGCO Swivel, new additions to our range! Powerhowse Electric is proud to work with our partners to supply reliable and quality products for your cable hauling needs. All Swivels are stringently quality tested and inspected to ensure optimum reliability and performance.

**Line Pulling Swivel – Galvanized** are designed to the highest specifications for underground and overhead pulling applications.

**Line Pulling Swivel – Bright Zinc Plated Steel** are designed for use in stringing high tension wires for electrical transmission and distribution. Swivels are important in pulling when the lines develop torsion during installation. Swivels will release torque and prevent it from reaching dangerous levels, which can cause damage to the cable.

**Directional Drilling Swivel** are designed for horizontal directional drilling or underground cable installation only. Use to counter rotational forces caused by boring. They can be greased for removal of dirt and contaminants.



**Line Pulling Swivel –  
Galvanized**



**Line Pulling Swivel –  
Bright Zinc Plated Steel**



**Directional Drilling  
Swivel**

CODE	DESCRIPTION	LENGTH	DIA	MAX ROPE DIA	U/G SWL	O/H SWL
ZSW2649	Line Pulling Galv 0.46kg	120mm	32mm	15mm	1814kgs	1088kgs
ZSW2929	Line Pulling Galv 0.80kg	136mm	38mm	16mm	3628kgs	2177kgs
ZSW6122	Line Pulling Galv 1.69kg	178mm	47mm	19mm	4535kgs	2721kgs
ZSW6123	Line Pulling Galv 4.17kg	259mm	62mm	25mm	7257kgs	4354kgs
ZSW2857	Line Pulling Galv 4.74kg	282mm	63mm	25mm	13,607kgs	8164kgs
ZSW2091	Line Pulling PS 0.19kg	85mm	22mm	10mm	1020kgs	612kgs
ZSW2092	Line Pulling PS 0.25kg	101mm	25mm	11mm	1587kgs	952kgs
ZSW2093	Line Pulling PS 0.51kg	126mm	32mm	14mm	2267kgs	1360kgs
ZSW2094	Line Pulling PS 0.65kg	132mm	35mm	14mm	3175kgs	1905kgs
ZSW2096	Line Pulling PS 1.07kg	155mm	41mm	18mm	4535kgs	2721kgs
ZSW2097	Line Pulling PS 2.08kg	186mm	53mm	20mm	6803kgs	4082kgs
ZSW11133	Directional Drilling 1133	183mm	41.2mm	16mm	8500kgs	N/A
ZSW11134	Directional Drilling 1134	211mm	50.8mm	19mm	4535kgs	N/A